

# Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

**Supplier's name or trade mark:** LEDVANCE

**Supplier's address:** LEDVANCE GmbH, Parkring 29-33, 85748 Garching, DE

**Model identifier:** AC57980

**Type of light source:**

|                                                     |       |                                 |     |
|-----------------------------------------------------|-------|---------------------------------|-----|
| Lighting technology used:                           | LED   | Non-directional or directional: | DLS |
| Light source cap-type (or other electric interface) | GU5.3 |                                 |     |
| Mains or non-mains:                                 | NMLS  | Connected light source (CLS):   | No  |
| Colour-tuneable light source:                       | No    | Envelope:                       | -   |
| High luminance light source:                        | No    |                                 |     |
| Anti-glare shield:                                  | No    | Dimmable:                       | Yes |

## Product parameters

| Parameter                                                                                                                                             | Value                     | Parameter                                                                                                                                                  | Value                  |
|-------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------|
| <b>General product parameters:</b>                                                                                                                    |                           |                                                                                                                                                            |                        |
| Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer                                                                         | 7                         | Energy efficiency class                                                                                                                                    | F                      |
| Useful luminous flux ( $\phi_{\text{use}}$ ), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) | 621 in Nar-row cone (90°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 4 000                  |
| On-mode power ( $P_{\text{on}}$ ), expressed in W                                                                                                     | 6,8                       | Standby power ( $P_{\text{sb}}$ ), expressed in W and rounded to the second decimal                                                                        | 0,00                   |
| Networked standby power ( $P_{\text{net}}$ ) for CLS, expressed in W and rounded to the second decimal                                                | -                         | Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set                                                         | 90                     |
| Outer dimensions without separate control gear, lighting control                                                                                      | Height                    | Spectral power distribution in the range 250 nm to 800 nm, at full-load                                                                                    | See image in last page |
|                                                                                                                                                       | Width                     |                                                                                                                                                            |                        |
|                                                                                                                                                       | Depth                     |                                                                                                                                                            |                        |


|                                                           |      |                                                                    |                |  |
|-----------------------------------------------------------|------|--------------------------------------------------------------------|----------------|--|
| parts and non-lighting control parts, if any (millimetre) |      |                                                                    |                |  |
| Claim of equivalent power <sup>(a)</sup>                  | Yes  | If yes, equivalent power (W)                                       | 50             |  |
|                                                           |      | Chromaticity coordinates (x and y)                                 | 0,386<br>0,373 |  |
| <b>Parameters for directional light sources:</b>          |      |                                                                    |                |  |
| Peak luminous intensity (cd)                              | 800  | Beam angle in degrees, or the range of beam angles that can be set | 36             |  |
| <b>Parameters for LED and OLED light sources:</b>         |      |                                                                    |                |  |
| R9 colour rendering index value                           | 45   | Survival factor                                                    | 0,90           |  |
| the lumen maintenance factor                              | 0,96 |                                                                    |                |  |

(a) : not applicable;

(b) : not applicable;



Model placed on the Union market from 13/11/2023



**EPREL registration number:** 1841957

<https://eprel.ec.europa.eu/qr/1841957>

**Supplier:** LEDVANCE GmbH (Manufacturer)

**Website:** <http://www.ledvance.com/>

**Customer care service:**

**Name:** LEDVANCE GmbH

**Website:** <http://www.ledvance.com/>

**Email:** [contact@ledvance.com](mailto:contact@ledvance.com)

**Phone:** +49 89-780673-100

**Address:**

Parkring 29-33  
85748 Garching  
Germany